Dear Friend:

Having your child in a safety seat while riding in a vehicle will not only help protect him or her from serious injury, it is also the law in California. A child passenger restraint system is required for any child who is under the age of six or weighs 60 pounds or less.

Child safety seats must be used correctly. It only takes one mistake in securing the seat or in securing your child to result in the safety seat failing to protect your child.

The National Highway Traffic Safety Administration (NHTSA) estimated in a 2005 study that 72.6 percent of child restraint systems displayed one or more critical misuses.

This brochure will assist you in selecting the right safety seat for your child and provide safety tips on how to secure child passengers. In addition to these tips, please read the instructions that came with your safety seat, and check your vehicle owner's manual to ensure that your child's safety seat is compatible with your automobile and is properly installed.

If you have any questions or concerns regarding child safety, please call my District Office at (760) 342-8047.

Sincerely,

V. MANUEL PÉREZ

Assemblymember, 80th District

V. Manuel laver



Compliments of

V. Manuel Pérez

ASSEMBLYMEMBER, 80TH DISTRICT

District Offices:

45-677 Oasis Street Indio, CA 92201 (760) 342-8047 • Fax: (760) 347-8704

Imperial Valley Office 1450 South Imperial Avenue El Centro, CA 92243 (760) 336-8912 • Fax: (760) 336-8914

Capitol Office:

State Capitol
P.O. Box 942849
Sacramento, CA 94249-0080
(916) 319-2080 • Fax: (916) 319-2180

E-mail:

Assemblymember.Manuel.Perez@assembly.ca.gov

Website:

www.asm.ca.gov/mperez

Assembly Website:

www.asm.ca.gov



Child Safety Seat Checklist

IS THE SEAT FACING THE RIGHT WAY?

- Babies must ride facing the rear until they weigh at least 18-20 pounds and can sit up well by themselves. Never place a child in the front passenger seat if your vehicle has a passenger-side airbag.
- Many seats convert from infant to toddler use. These convertibles should not be turned to face forward until the child weighs at least 18-20 pounds and can sit up.

IS YOUR CHILD PROPERLY SECURED?

- The shoulder harness should go through slots level with or just above the shoulders.
- The webbing must lie flat, not twisted.
- Straps must fit snugly. Readjust to allow for the thickness of your child's clothes.
- The crotch strap should be kept short. The retainer strap or plastic clip, if provided, should be high enough to keep the harness from slipping off the shoulders.
- If the seat has a shield, it should fit close to the child's body and not be used without the harness.

IS THE SAFETY BELT IN THE RIGHT PLACE?

Each model has its own correct belt route. Don't guess. To protect your child, follow the installation instructions.

IS THE BELT TIGHT ENOUGH?

- ✓ Check before each trip.
- Convertible models usually have different belt routes for use when facing forward or facing the rear. Test by pushing the seat forward and backward. It should not move. If the seat moves, tighten the belt while pressing the safety seat firmly into the auto seat cushion with your knee.
- If the belt has a windup reel, feed the webbing back into it to take up all the slack.

Choose the Right Safety Seat for Your Child

INFANT SAFETY SEATS

Infant-only safety seats can be used by infants up to 20 pounds, a weight usually reached between four and twelve months. The seat must be reclined halfway and must be facing the rear of the car. Be sure the harness goes over the infant's shoulders and is buckled between the legs.

CONVERTIBLE OR TODDLER SAFETY SEATS

Convertible safety seats can be used from birth until a child weighs 60 or more pounds. For infants who weigh less than 20 pounds, the seat must face the rear and be reclined halfway. Be sure the harness goes over the infant's shoulders and is buckled between the legs. If you decide to buy a convertible seat for a newborn, be sure to buy a simple "five-point harness" system. If an infant is very little, the regular "three-point harness" system will not properly secure the child.

For toddlers who weigh between 20 and 40 pounds, the seat must face forward and be in the upright position, and the harness must be put through the strap slots. Review the instruction booklet to find out exactly where to strap the vehicle safety belt.

BOOSTER SAFETY SEATS

Children over 40 pounds should be correctly secured in belt positioning booster seats until the adult lap and shoulder belts fit correctly.

By elevating the child, a booster seat aligns the shoulder belt across the collar bone and shoulder, as well as helps to keep the lap belt low on the child's hips.



The safest booster seat to choose is one with a removable shield. If your car comes with a shoulder/lap belt, then a removable shield may not be necessary.

Never use a cushion, household booster, or a homemade booster in a car.

VEHICLE SAFETY BELTS

Safety belts are permitted for children four years and older who weigh at least 60 pounds, but they should only be used if they fit your particular child correctly. The lap belt must fit your child in two ways. First, it must sit low across the child's hips (not across the stomach) and second, the shoulder belt must lay across the collar bone and shoulder (not crossing the neck or face). If these two conditions are not met, then your child should still be sitting in a booster seat.

SAFETY SEAT CHECKS

Most California Highway Patrol offices offer inspections to ensure your child's seat is properly installed. Call your nearest CHP office for more information.

Indio	(760)	77	2-8911
Blythe	(760)	92	22-6141
El Centro	(760)	48	2-2500
Winterhaven	(760)	57	2-0294